

View Online at <https://aerobasegroup.com/nsn/4820-00-125-7902>

**Pipe Size Accommodated:**

0.250 inches 2nd end

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Integral

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

225.0 degrees fahrenheit 2nd response

**Connection Style:**

Plain (pipe) 2nd end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Valve stem lock shield and bonnet packing and pressure tight outlet side

**Thready Qty Per Inch (tpi):**

18 1st end

**Adjustable Pressure Range:**

+1500.0/+2750.0 pounds per square inch

**Maximum Operating Pressure:**

2750.0 pounds per square inch single response

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.375 inches 1st end

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.