

View Online at <https://aerobasegroup.com/nsn/4820-00-125-7902>

Pipe Size Accommodated:

0.250 inches 2nd end

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit 2nd response

Connection Style:

Plain (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

18 1st end

Adjustable Pressure Range:

+1500.0/+2750.0 pounds per square inch

Maximum Operating Pressure:

2750.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Stainless steel flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.