NSN 4820-00-125-8082

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-125-8082

Flow Control Device:
Disk
Maximum Operating Temp:
150.0 degrees fahrenheit 2nd response
Connection Style:
Socket (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal tube all ends
Mounting Position:
Horizontal
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter Tube Accommodated:
0.500 inches all ends
Material:
Material: Copper alloy
Copper alloy
Copper alloy Media For Which Designed:
Copper alloy Media For Which Designed: Water, fresh 2nd response
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator:
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life:
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization:
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: No
Copper alloy Media For Which Designed: Water, fresh 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: