NSN 4820-00-131-5072

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-131-5072

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
450.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Opening Pressure Setting:
150.0 pounds per square inch
Special Features:
Designed for acetylene, gaseous ammonia, air, hydrogen, refrigerant 12, and inert gas
Material:
Aluminum alloy 2024 and rubber butadiene-acrylonitrile class nbr flow control device
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-00-131-5072

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0