## NSN 4820-00-133-0798

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-133-0798

Right-hand all ends  Flow Control Device:  Poppet  Disk Loading Method:  Spring  Maximum Operating Temp:  225.0 degrees fahrenheit single response  Connection Style:  Plain, optional end (pipe) all ends  Valve Operation Method:
Poppet  Disk Loading Method: Spring  Maximum Operating Temp: 225.0 degrees fahrenheit single response  Connection Style: Plain, optional end (pipe) all ends  Valve Operation Method:
Disk Loading Method: Spring Maximum Operating Temp: 225.0 degrees fahrenheit single response Connection Style: Plain, optional end (pipe) all ends Valve Operation Method:
Spring  Maximum Operating Temp: 225.0 degrees fahrenheit single response  Connection Style: Plain, optional end (pipe) all ends  Valve Operation Method:
Maximum Operating Temp: 225.0 degrees fahrenheit single response Connection Style: Plain, optional end (pipe) all ends Valve Operation Method:
225.0 degrees fahrenheit single response  Connection Style:  Plain, optional end (pipe) all ends  Valve Operation Method:
Connection Style: Plain, optional end (pipe) all ends Valve Operation Method:
Plain, optional end (pipe) all ends  Valve Operation Method:
Valve Operation Method:
A
Automatic
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
25.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Copper alloy
Media For Which Designed:
Nitrogen, gaseous 5th response
Style Designator:
Straight thru
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: