NSN 4820-00-134-4475

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-134-4475 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) 1st end **Valve Operation Method:** Automatic or manual **Connection Type:** Threaded internal boss 1st end **Mounting Facility: Bracket Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Center To Center Distance:** 1.500 inches Material: Steel comp 440a flow control device Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru

Thread Series Designator: Unjf 1st end

NSN 4820-00-134-4475

Lift-check Valve - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0