## NSN 4820-00-136-4832

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-136-4832

Pipe Size Accommodated:

0.250 inches all ends

**Thread Direction:** 

Right-hand all ends

Flow Control Device:

Disk

**Disk Loading Method:** 

Spring

Valve Discharge Flow Rate:

100.0 cubic feet per minute

**Connection Style:** 

Plain, optional en (pipe) all ends

#### Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

#### **Features Provided:**

Pressure tight outlet side

#### Adjustable Pressure Range:

+4000.0 to 10000.0 pounds per square inch

## Maximum Operating Pressure:

10000.0 pounds per square inch single response

#### **Thread Size:**

0.250 inches all ends

#### **Opening Pressure Setting:**

4000.0 pounds per square inch

Material:

Stainless steel

**Material Specification:** 

300seriescommercial mfr ref single material response

## Media For Which Designed:

Water, fresh single response

## Surface Treatment:

Passivate

Style Designator:

Angle

**Thread Series Designator:** 

Npt all ends

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 4820-00-136-4832

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

