NSN 4820-00-137-1835

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-137-1835

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end Flow Control Device:
Poppet Rennet Type:
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded Pick Loading Mathada
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Adjustable Pressure Range:
+10.0 to 50.0 pounds per square inch
Maximum Operating Pressure:
50.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
35.0 pounds per square inch
Material:
Steel comp 303 flow control device
Material Specification:
Fedstd66, aisi303/sae30303 federal standard single material response flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Angle
Thread Series Designator:
Anpt 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-137-1835

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0