NSN 4820-00-137-1835

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-137-1835

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Adjustable Pressure Range:

+10.0 to 50.0 pounds per square inch

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Opening Pressure Setting:

35.0 pounds per square inch

Material:

Steel comp 303 flow control device

Material Specification:

Fedstd66, aisi303/sae30303 federal standard single material response flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Angle

Thread Series Designator:

Anpt 2nd end

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-137-1835

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

