NSN 4820-00-137-7991

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-137-7991 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **Valve Operation Method:** Automatic Flange Shape: Round 1st end **Connection Type:** Flange 1st end **Features Provided:** Bonnet packing and pressure tight outlet side Adjustable Pressure Range: +163.0/+186.0 pounds per square inch **Maximum Operating Pressure:** 210.0 pounds per square inch single response **Criticality Code Justification:** Zzzy **Opening Pressure Setting:** 175.0 pounds per square inch Flange Face Design: Plain 1st end Material: Nickel alloy stem Media For Which Designed: Water, fresh single response **Style Designator:** Angle **Reference Number Differentiating Characteristics:** Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4820-00-137-7991

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0