

View Online at <https://aerobasegroup.com/nsn/4820-00-138-3870>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

5.000 inches

Maximum Operating Pressure:

225.0 pounds per square inch 2nd response

Outside Diameter:

10.000 inches all ends

Face To Face Distance:

13.000 inches

Thickness:

0.750 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

8.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-c-390, alloy d4 federal specification single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0