NSN 4820-00-138-3883

Check Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-138-3883

Disk Loading Method:
Weight
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
6.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
11.000 inches all ends
Face To Face Distance:
14.000 inches
Thickness:
0.938 inches all ends
Bolt Hole Diameter:
0.875 inches all ends
Bolt Circle Diameter:
9.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
8.500 inches all ends
Material:
Steel body
Material Specification:

Astm a216, grade wcb assn standard single material response body

NSN 4820-00-138-3883

Check Valve - Page 2 of 2



Media	For	Which	Design	ed:
ricaia		*****	Design	cu.

Steam single response

Style Designator:

Straight through flanged ends

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

C group and 3 type and 5 trim and 150 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0