## NSN 4820-00-138-3883

Check Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-138-3883

Disk Loading Method:
Weight
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
6.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
11.000 inches all ends
Face To Face Distance:
14.000 inches
Thickness:
0.938 inches all ends
<b>Bolt Hole Diameter:</b>
0.875 inches all ends
<b>Bolt Circle Diameter:</b>
9.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
8.500 inches all ends
Material:
Steel body
Material Specification:

Astm a216, grade wcb assn standard single material response body

## NSN 4820-00-138-3883

Check Valve - Page 2 of 2



Media	For	Which	Design	ed:
ricaia		*****	Design	cu.

Steam single response

**Style Designator:** 

Straight through flanged ends

## **Test Data Document:**

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Or Standard:**

C group and 3 type and 5 trim and 150 class

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A530b0