# NSN 4820-00-138-3884

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-138-3884

Flow Control Device: Disk Disk Loading Method: Weight Renewable Seat Ring Type: Threaded Bolt Hole Quantity:
Disk Loading Method: Weight Renewable Seat Ring Type: Threaded
Weight Renewable Seat Ring Type: Threaded
Renewable Seat Ring Type: Threaded
Threaded
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
13.500 inches all ends
Face To Face Distance:
19.500 inches
Thickness:
1.063 inches all ends
Bolt Hole Diameter:
0.875 inches all ends
Bolt Circle Diameter:
11.750 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
0.625 inches all ends
Special Features:
Valve size 8.000 in.
Material:
Steel body
Material Specification:
Astm a216, grade wcb assn standard single material response body

# NSN 4820-00-138-3884

Check Valve - Page 2 of 2



### Media For Which Designed:

Steam single response

### Style Designator:

Straight thru

#### Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Or Standard:**

C group and 3 type and 5 trim and 150 class

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A530b0