

View Online at <https://aerobasegroup.com/nsn/4820-00-138-8029>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.500 inches

Maximum Operating Pressure:

225.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.000 inches

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight through flanged ends

Specification Data:

59646-mss-sp-80 professional/industrial association standard

Specification Or Standard:

150 class and flange end and 3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0