NSN 4820-00-139-3293



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-139-3293 **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 14.0 gallons per minute **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Pressure tight outlet side **Thread Size:** 0.750 inches all ends Material: Steel Media For Which Designed: Oil, hydraulic single response **Surface Treatment:** Primer and paint **Surface Treatment Specification:** Mil-p-52192, air drying military specification 1st treatment response and mil-p-52227, color 24087 federal standard 595 military specification 2nd treatment response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4820-00-139-3293

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-p-52192 spec.