NSN 4820-00-139-5956



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-139-5956 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 240.0 degrees fahrenheit single response **Connection Style:** External seat for gasket seal (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 1st end Thready Qty Per Inch (tpi): 20 1st end Adjustable Pressure Range: +25.0 to 75.0 pounds per square inch **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Opening Pressure Setting:** 31.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material:

Aluminum alloy 2024 body

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

NSN 4820-00-139-5956

Safety Relief Valve - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.