## NSN 4820-00-142-1014

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-142-1014

Pipe Size Accommodated:
0.500 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 2nd end
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing
Adjustable Pressure Range:
+31.0/+50.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.500 inches 1st end
Outside Diameter:
3.875 inches 2nd end
Thickness:
0.438 inches 2nd end
Bolt Hole Diameter:
0.500 inches 2nd end
Bolt Circle Diameter:
2.750 inches 2nd end
Flange Face Design:
Raised straight 2nd end

## NSN 4820-00-142-1014

Safety Relief Valve - Page 2 of 2



Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
1.688 inches 2nd end
Material:
Steel body
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0