

View Online at <https://aerobasegroup.com/nsn/4820-00-142-1380>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Valve stem lock shield

Adjustable Pressure Range:

+125.0 to 160.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

5.062 inches all ends

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

3.938 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Material Specification:

Mil-s-870 military specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-870 spec.