NSN 4820-00-142-1410

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-142-1410

Pipe Size Accommodated:						
0.750 inches all ends						
Thread Direction:						
Right-hand all ends						
Flow Control Device:						
Poppet						
Bonnet Type:						
Exposed spring						
Bonnet Attachment Method:						
Bolted						
Disk Loading Method:						
Spring						
Maximum Operating Temp:						
150.0 degrees fahrenheit single response						
Connection Style:						
Plain, optional en (pipe) all ends						
Valve Operation Method:						
Automatic						
Connection Type:						
Threaded internal pipe all ends						
Features Provided:						
Pressure tight outlet side						
Thready Qty Per Inch (tpi):						
14 all ends						
Adjustable Pressure Range:						
+100.0 to 400.0 pounds per square inch						
Maximum Operating Pressure:						
400.0 pounds per square inch single response						
Thread Size:						
0.750 inches all ends						
Material:						
Copper alloy						
Media For Which Designed:						
Water, fresh single response						
Style Designator:						
Angle						
Thread Series Designator:						
Npt all ends						
Specification Or Standard:						
A2 type and c class						
Shelf Life:						
N/a						

NSN 4820-00-142-1410

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0