# NSN 4820-00-142-1541

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-142-1541

Flow Control Device: Disk

Bonnet Type:

Inside spring

**Bonnet Attachment Method:** 

Threaded

## **Disk Loading Method:**

Spring

**Bolt Hole Quantity:** 

4 all ends

### Maximum Operating Temp:

500.0 degrees fahrenheit single response

### Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

**Connection Type:** 

Flange all ends

**Features Provided:** 

Bonnet packing and pressure tight outlet side

# Adjustable Pressure Range:

+121.0 to 160.0 pounds per square inch

# Maximum Operating Pressure:

150.0 pounds per square inch single response

**Outside Diameter:** 

6.000 inches all ends

Thickness:

0.500 inches all ends

**Bolt Hole Diameter:** 

0.750 inches all ends

#### Bolt Circle Diameter:

4.750 inches all ends

#### Flange Face Design:

Raised straight all ends

#### **Raised Face Height:**

0.062 inches all ends

# Raised Face Diameter:

3.625 inches all ends

## **Special Features:**

2 in. Valve size

Material:

Stainless steel stem



# NSN 4820-00-142-1541

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Steam single response

Style Designator:

Angle

Specification Or Standard:

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0