

View Online at <https://aerobasegroup.com/nsn/4820-00-142-1547>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

3 2nd end

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Adjustable Pressure Range:

+276.0/+450.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

4.000 inches 1st end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

3.000 inches

Bolt Hole Diameter:

0.562 inches 2nd end

Second Connection Face To Centerline Distance:

3.000 inches

Bolt Circle Diameter:

2.875 inches 1st end

Flange Face Design:

Plain 2nd end

Material:

Steel uns j03008 body

Material Specification:

Mil-s-15083 military specification single material response body

Media For Which Designed:

Oil single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-15083 spec.