## NSN 4820-00-145-6265

Check Valve - Page 1 of 2

Unf 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-145-6265

Pipe Size Accommodated:
0.125 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional end (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Mounting Position:
Horizontal
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.125 inches 1st end
Material:
Steel flow control device
Material Specification:
Qq-a-225/4, alloy 2014 federal specification 1st material response body and qq-a0225/5, alloy 2017 federal specification 2nd material
response body and qq-a-225/6, alloy 2024 federal specification 3rd material response body
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:

## NSN 4820-00-145-6265

Check Valve - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-p-5315 spec.

Shelf Life: