NSN 4820-00-146-9339

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-146-9339

Flow Control Device:
Disk or stem
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Mounting Facility:
Bracket
Valve Size:
2.000 inches
Outside Diameter:
8.500 inches 2nd end
Thickness:
0.937 inches 1st end
First Connection Face To Centerline Distance:
6.375 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
6.062 inches
Bolt Circle Diameter:
6.500 inches 2nd end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
0.937 inches 1st end
Special Features:
Venturi nozzle design on second end
Style Designator:
Angle flanged ends

NSN 4820-00-146-9339

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0