## NSN 4820-00-146-9341

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-146-9341

Flow Control Device:
Disk or stem
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
9 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Mounting Facility:
Bracket
Valve Size:
1.500 inches
Outside Diameter:
9.625 inches 1st end
Thickness:
1.625 inches 1st end
First Connection Face To Centerline Distance:
7.000 inches
Bolt Hole Diameter:
1.062 inches 1st end
Second Connection Face To Centerline Distance:
7.750 inches
Bolt Circle Diameter:
7.687 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.687 inches 1st end
Raised Face Diameter:
6.375 inches 1st end
Style Designator:
Angle flanged ends
Shelf Life:
N/a

## NSN 4820-00-146-9341

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0