NSN 4820-00-146-9352

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-146-9352

Pipe Size Accommodated:
1.500 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Disk Loading Method:
Weight
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Socket (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe 1st end
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Maximum Operating Pressure:
700.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Material:
Nickel alloy 400 stem or nickel alloy r-405 stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Straight thru
Reference Number Differentiating Characteristics:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 4820-00-146-9352

Stop-check Valve - Page 2 of 2



Fiig:

A530b0