

View Online at <https://aerobasegroup.com/nsn/4820-00-147-5088>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.500 inches

Thickness:

0.688 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

4.125 inches all ends

Material:

Stainless steel stem

Material Specification:

Astm a105, grade 2 assn standard single material response body

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0