

View Online at <https://aerobasegroup.com/nsn/4820-00-155-5672>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-65.0 degrees fahrenheit

**Connection Style:**

Flareless all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

12.0 degrees all ends

**Material:**

Steel comp 440c flow control device

**Media For Which Designed:**

Hydraulic fluid, petroleum base single response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Unf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530b0

**Mil-std (military Standard):**

Mil-s-5002 spec.