## NSN 4820-00-155-7681

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-155-7681 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 450.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 12 2nd end **Thread Size:** 1.062 inches 2nd end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 30.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.750 inches 2nd end Material: Steel comp 303 **Material Specification:** Fedstd66, aisi303/sae30303 federal standard all material responses Media For Which Designed: Water-oil-gas single response **Style Designator:** 

Err-090

Thread Series Designator:
Unj 2nd end

## NSN 4820-00-155-7681

Safety Relief Valve - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0