## NSN 4820-00-158-1229

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-158-1229

Body Material:
Steel
Body Style:
Straight thru
Media For Which Designed:
Hydraulic oil
First End Connection Type:
Threaded internal pipe
First End Style Designator:
Flare
First End Thread Size And Series/type Designator:
0.250-18 nptf
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Not identical
Second End Connection Type:
Threaded internal pipe
Second End Style Designator:
Plain
Second End Thread Size And Series/type Designator:
0.250-18 nptf
Second End Thread Direction:
Right-hand
First End Seat Angle In Deg:
45.0
Flow Control Device:
Needle
Flow Control Device Material:
Steel
End Connection Quantity:
2
Valve Discharge Flow Rate:
5.0 gallons per minute
Regulation Type:
1st stage manual, 2nd stage automatic
Manual Control Method:
Knob
Maximum Inlet Pressure Rating:
5000.0 pounds per square inch
Tempurature Rating:
Between -25.0 degrees fahrenheit and 120.0 degrees fahrenheit

## NSN 4820-00-158-1229

Calibrated Flow Valve - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A21100