NSN 4820-00-159-8562

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-159-8562

Flow Control Device:
Needle
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Valve Size:
0.500 inches
Maximum Operating Pressure:
850.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Outside Diameter:
4.750 inches 1st end
Thickness:
0.875 inches 1st end
Bolt Hole Diameter:
0.812 inches 1st end
Bolt Circle Diameter:
3.250 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.000 inches
Material:
Steel stem
Steel stem Media For Which Designed:

NSN 4820-00-159-8562

Globe Valve - Page 2 of 2



Style	Desia	nator:

Straight through flanged ends

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A046b0