## NSN 4820-00-161-1638

Restrictor Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-161-1638

| Thread Class:                                   |
|---|
| 3a all ends                                     |
| Thread Direction:                               |
| Right-hand all ends                             |
| Maximum Operating Temp:                         |
| 275.0 degrees fahrenheit single response        |
| Minimum Operating Temp:                         |
| -65.0 degrees fahrenheit                        |
| Connection Style:                               |
| Flareless all ends                              |
| Valve Operation Method:                         |
| Automatic                                       |
| Connection Type:                                |
| Threaded external tube all ends                 |
| Mounting Position:                              |
| Horizontal or vertical                          |
| Maximum Operating Pressure:                     |
| 3000.0 pounds per square inch single response   |
| Thread Size:                                    |
| 0.562 inches 1st end                            |
| Seat Angle:                                     |
| 12.0 degrees all ends                           |
| Material:                                       |
| Steel comp 303 flow control device              |
| Media For Which Designed:                       |
| Hydraulic fluid, petroleum base single response |
| Surface Treatment:                              |
| Anodize   |
| Style Designator:                               |
| Straight thru                                   |
| Thread Series Designator:                       |
| Unf all ends                                    |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |
| Fiig:   |
| A530b0  |
|   |
|   |