## NSN 4820-00-163-0226

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-163-0226

Pipe Size Accommodated:
0.250 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+40.0 to 125.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Opening Pressure Setting:
90.0 pounds per square inch
Material:
Steel comp 316 flow control device
Material Specification:
Fedstd66, aisi316/sae30316 federal standard single material response flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon 1st response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

## NSN 4820-00-163-0226

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0