NSN 4820-00-163-5162

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-163-5162

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
42500.0 pounds per hour
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
9 1st end
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Pressure tight outlet side
Valve Size:
2.500 inches
Opening Pressure Setting:
700.0 pounds per square inch
Outside Diameter:
8.688 inches 1st end
Thickness:
1.125 inches 2nd end
Bolt Hole Diameter:
0.812 inches 2nd end
Bolt Circle Diameter:
7.125 inches 1st end
Flange Face Design:
Plain 2nd end
Special Features:
The end connection identified above as the second end is the valve inlet
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
As differentiated by the value discharge flow acts as a vice and

As differentiated by the valve discharge flow rate requirement

NSN 4820-00-163-5162

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0