

View Online at <https://aerobasegroup.com/nsn/4820-00-163-5164>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

15000.0 pounds per hour

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 2nd end

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Features Provided:

Pressure tight outlet side

Valve Size:

1.500 inches

Opening Pressure Setting:

1340.0 pounds per square inch

Outside Diameter:

7.500 inches 2nd end

Bolt Hole Diameter:

1.125 inches 1st end

Bolt Circle Diameter:

5.875 inches 2nd end

Flange Face Design:

Recessed straight 1st end

Raised Face Height:

0.062 inches 2nd end

Raised Face Diameter:

4.125 inches 2nd end

Recess Diameter:

6.125 inches 1st end

Recess Depth:

0.062 inches 1st end

Material:

Steel uns j12070 body

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0