## NSN 4820-00-163-5164

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-163-5164

Flow Control Device:				
Disk				
Bonnet Type:				
Exposed spring				
Bonnet Attachment Method:				
Bolted				
Disk Loading Method:				
Spring				
Valve Discharge Flow Rate:				
15000.0 pounds per hour				
Renewable Seat Ring Type:				
Threaded				
Bolt Hole Quantity:				
8 2nd end				
Valve Operation Method:				
Automatic or manual				
Flange Shape:				
Round with holes all ends				
Features Provided:				
Pressure tight outlet side				
Valve Size:				
1.500 inches				
Opening Pressure Setting:				
1340.0 pounds per square inch				
Outside Diameter:				
7.500 inches 2nd end				
<b>Bolt Hole Diameter:</b>				
1.125 inches 1st end				
Bolt Circle Diameter:				
5.875 inches 2nd end				
Flange Face Design:				
Recessed straight 1st end				
Raised Face Height:				
0.062 inches 2nd end				
Raised Face Diameter:				
4.125 inches 2nd end				
Recess Diameter:				
6.125 inches 1st end				
Recess Depth:				
0.062 inches 1st end				
Material:				
Steel uns j12070 body				

## NSN 4820-00-163-5164

Safety Relief Valve - Page 2 of 2



•	_		
Style	D)es	sıan	ator:
,		J. 9.	

Angle flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0