NSN 4820-00-163-5170

Safety Relief Valve - Page 1 of 2

Flow Control Device:

View Online at https://aerobasegroup.com/nsn/4820-00-163-5170



Disk **Bonnet Type:** Exposed spring **Bonnet Attachment Method:** Bolted **Disk Loading Method:** Spring Valve Discharge Flow Rate: 8544.0 pounds per hour **Renewable Seat Ring Type:** Threaded **Bolt Hole Quantity:** 8 2nd end Valve Operation Method: Automatic or manual Flange Shape: Round with holes 2nd end **Features Provided:** Pressure tight outlet side Valve Size: 1.500 inches **Opening Pressure Setting:** 705.0 pounds per square inch **Outside Diameter:** 7.500 inches 2nd end **Bolt Hole Diameter:** 0.875 inches 2nd end **Bolt Circle Diameter:** 5.875 inches 2nd end Flange Face Design: Recessed straight 1st end **Raised Face Height:** 0.062 inches 2nd end **Raised Face Diameter:** 4.125 inches 2nd end **Recess Depth:** 0.062 inches 1st end Style Designator: Angle flanged ends **Reference Number Differentiating Characteristics:** As differentiated by the valve discharge flow rate requirement

NSN 4820-00-163-5170

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

