NSN 4820-00-163-5180

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk

View Online at https://aerobasegroup.com/nsn/4820-00-163-5180



Exposed spring **Bonnet Attachment Method:** Bolted **Disk Loading Method:** Spring Valve Discharge Flow Rate: 59900.0 pounds per hour **Renewable Seat Ring Type:** Threaded **Bolt Hole Quantity:** 8 2nd end Valve Operation Method: Automatic or manual Flange Shape: Round with holes 2nd end **Features Provided:** Pressure tight outlet side Valve Size: 2.500 inches **Opening Pressure Setting:** 1350.0 pounds per square inch **Outside Diameter:** 9.625 inches 1st end Thickness: 1.688 inches 1st end **Bolt Hole Diameter:** 1.125 inches 1st end **Bolt Circle Diameter:** 7.500 inches 1st end Flange Face Design: Recessed straight 1st end **Raised Face Height:** 0.062 inches 2nd end **Raised Face Diameter:** 6.188 inches 2nd end **Recess Diameter:** 8.750 inches 1st end **Recess Depth:** 0.062 inches 1st end

NSN 4820-00-163-5180

Safety Relief Valve - Page 2 of 2



Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by the valve discharge flow rate requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0