## NSN 4820-00-163-5745

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-163-5745

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic  Connection Type:
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+115.0 to 250.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Opening Pressure Setting:
180.0 pounds per square inch
Special Features:
The end connection identified above as the second end is the valve inlet
Material:
Steel comp 303 flow control device and plastic polytetrafluoroethylene flow control device
Material Specification:
Qq-s-764, type303-canceled federal specification 1st material response flow control device
Media For Which Designed:
Air 1st response
Style Designator:
Angle
Thread Series Designator:
Anpt 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-163-5745

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0