## NSN 4820-00-163-9272

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-163-9272

| Thread Class:  |
|--|
| 3a 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Flow Control Device:   |
| Disk   |
| Disk Loading Method:   |
| Spring   |
| Renewable Seat Ring Type:  |
| Pressed-in   |
| Maximum Operating Temp:  |
| 160.0 degrees fahrenheit 2nd response                                      |
| Connection Style:  |
| Flared (tube) 1st end  |
| Valve Operation Method:  |
| Automatic  |
| Connection Type:   |
| Threaded external tube 1st end   |
| Mounting Position:   |
| Horizontal or vertical   |
| Thready Qty Per Inch (tpi):  |
| 12 2nd end   |
| Maximum Operating Pressure:  |
| 400.0 pounds per square inch single response                               |
| Thread Size:   |
| 2.250 inches 2nd end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Outside Diameter Tube Accommodated:  |
| 1.750 inches 2nd end   |
| Material:  |
| Rubber synthetic seat  |
| Material Specification:  |
| Qq-a-225/6, alloy 2024 federal specification single material response body |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon 2nd response   |
| Surface Treatment:   |
| Anodize  |
| Style Designator:  |
| Straight thru  |
| Thread Series Designator:  |
| Un 2nd end   |

## NSN 4820-00-163-9272

Check Valve - Page 2 of 2



| he |  |  |
|----|--|--|
|    |  |  |
|    |  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0