NSN 4820-00-164-6523

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-164-6523

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional end (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.500 inches 1st end
Material:
Material: Stainless steel flow control device
Stainless steel flow control device
Stainless steel flow control device Surface Treatment:
Stainless steel flow control device Surface Treatment: Anodize
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No
Stainless steel flow control device Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: