NSN 4820-00-165-1548

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-165-1548

Flow Control Device:				
Disk				
Bonnet Type:				
Exposed spring				
Bonnet Attachment Method:				
Bolted				
Disk Loading Method:				
Spring				
Valve Discharge Flow Rate:				
50000.0 pounds per hour				
Renewable Seat Ring Type:				
Threaded				
Bolt Hole Quantity:				
8 2nd end				
Valve Operation Method:				
Automatic or manual				
Flange Shape:				
Round with holes 2nd end				
Features Provided:				
Pressure tight outlet side				
Valve Size:				
2.500 inches				
Opening Pressure Setting:				
740.0 pounds per square inch				
Outside Diameter:				
9.000 inches 2nd end				
Bolt Hole Diameter:				
0.875 inches 2nd end				
Bolt Circle Diameter:				
7.250 inches 2nd end				
Flange Face Design:				
Recessed straight 1st end				
Raised Face Height:				
0.062 inches 2nd end				
Raised Face Diameter:				
5.500 inches 2nd end				
Recess Diameter:				
6.875 inches 1st end				
Recess Depth:				
0.062 inches 1st end				
Style Designator:				
Angle flanged ends				

NSN 4820-00-165-1548

Safety Relief Valve - Page 2 of 2



Reference	Number	Differentiating	Characteristics:
11010101100	HUIIDEI	Differentiation	Ullai actel istics.

As differentiated by the valve discharge flow rate requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0