# NSN 4820-00-167-3741

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-167-3741

Thread Class:

3a 1st end

**Thread Direction:** 

Right-hand 1st end

# Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

280.0 degrees fahrenheit single response

**Connection Style:** 

Plain (tube) 1st end

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external tube 1st end

## Maximum Operating Pressure:

200.0 pounds per square inch single response

#### Thread Size:

0.437 inches 1st end

#### **Opening Pressure Setting:**

45.0 pounds per square inch

## **Outside Diameter Tube Accommodated:**

0.250 inches 1st end

#### **Special Features:**

Valve size 0.250 in.

#### Material:

Steel comp 303se

#### **Material Specification:**

Qq-s-764, type 303se-canceled federal specification single material response

#### Media For Which Designed:

Hydrogen 3rd response

#### Style Designator:

Straight through note: to be used for valve bodies of one section only.

# Thread Series Designator:

Unjf 1st end

# Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 4820-00-167-3741

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

