

View Online at <https://aerobasegroup.com/nsn/4820-00-168-2057>

Pipe Size Accommodated:

0.375 inches all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Spool

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.0 gallons per minute

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+25.0 to 1000.0 pounds per square inch

Maximum Operating Pressure:

1000.0 pounds per square inch single response

Thread Size:

0.375 inches all ends

Opening Pressure Setting:

100.0 pounds per square inch

Special Features:

W/handknob and buna-n seals

Material:

Steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Style Designator:

Angle

Thread Series Designator:

Nptf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0