NSN 4820-00-171-3026

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-171-3026

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Minimum Operating Temp:
-65.0 degrees fahrenheit
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees all ends
Material:
Steel comp 303 seat
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-171-3026

Check Valve - Page 2 of 2



em			

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.