NSN 4820-00-172-9122

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-172-9122

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
18882.0 pounds per hour
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 2nd end
End Application:
Hayes class t-ag 195
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Pressure tight outlet side
Valve Size:
1.500 inches
Criticality Code Justification:
Feat
Opening Pressure Setting:
643.0 pounds per square inch
Outside Diameter:
7.500 inches 1st end
Thickness:
1.312 inches 2nd end
Bolt Hole Diameter:
1.125 inches 2nd end
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.062 inches 1st end

NSN 4820-00-172-9122

Safety Relief Valve - Page 2 of 2



Raised Face Dian	neter:
------------------	--------

5.000 inches 1st end

Special Features:

Weapon system essential

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0