

View Online at <https://aerobasegroup.com/nsn/4820-00-173-7381>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

0.5 gallons per minute

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

External seat for gasket seal (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded cartridge all ends

Thready Qty Per Inch (tpi):

118 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Opening Pressure Setting:

185.0 pounds per square inch

Material:

Steel comp 440c flow control device

Material Specification:

Qq-s-763 federal specification single material response flow control device

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Screw-in cartridge

Thread Series Designator:

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.