NSN 4820-00-174-2437

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-174-2437

Pipe Size Accommodated:
0.500 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
312.0 cubic feet per minute
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 1st end
Power Drive Operating Pressure:
350.0 pounds per square inch
Adjustable Pressure Range:
+251.0/+400.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Opening Pressure Setting:
350.0 pounds per square inch
Material:
Copper alloy body
Material Specification:
Qq-c-390, alloy d4 federal specification single material response stem
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-174-2437

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0