

View Online at <https://aerobasegroup.com/nsn/4820-00-175-4796>

**Flow Control Device:**

Disk

**Bonnet Type:**

Exposed spring

**Bonnet Attachment Method:**

Bolted

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

39500.0 pounds per hour

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

9 1st end

**Valve Operation Method:**

Automatic or manual

**Flange Shape:**

Round with holes 2nd end

**Connection Type:**

Flange 1st end

**Features Provided:**

Pressure tight outlet side

**Valve Size:**

2.500 inches

**Opening Pressure Setting:**

685.0 pounds per square inch

**Outside Diameter:**

8.688 inches 1st end

**Thickness:**

1.188 inches 2nd end

**First Connection Face To Centerline Distance:**

5.968 inches

**Bolt Hole Diameter:**

0.812 inches 2nd end

**Second Connection Face To Centerline Distance:**

5.250 inches

**Bolt Circle Diameter:**

7.125 inches 1st end

**Flange Face Design:**

Plain 2nd end

**Special Features:**

The end connection identified above as the second end is the valve inlet

**Material:**

Stainless steel stem

**Style Designator:**

Angle flanged ends

**Reference Number Differentiating Characteristics:**

As differentiated by the valve discharge flow rate requirement

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0