

View Online at <https://aerobasegroup.com/nsn/4820-00-175-6228>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.312 inches all ends

Seat Angle:

45.0 degrees all ends

Outside Diameter Tube Accommodated:

1.000 inches all ends

Special Features:

Bulkhead threads on 1st fluid end connection; lave anodize gold

Material:

Steel stem

Material Specification:

Qq-s-763, cond a federal specification single material response flow control device

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.